

## BENEFITS

### Flexibility:

- Three battery-backed UPS outlets, and one surge protection-only outlet differentiated by color.
- USB port, MultiLink Software shutdown software, and USB cable.
- User replaceable batteries.

### Higher Availability:

- Up to five minutes of battery backup time at full load.
- Full sequenced battery testing to ensure batteries are available when needed.
- Advance early warning of UPS shutdown.
- RJ-45 port for data line surge protection.
- Site wiring fault indicator (120VAC only).

### Lowest Total Cost of Ownership:

- Two-Year replacement warranty.
- Optional one year or three year warranty extensions.

Liebert PSP is an economical, full featured UPS that delivers cost-effective power protection in a compact package.

The UPS provides battery-backed outlets and a surge protection-only outlet. The UPS battery offers up to five minutes of backup power at full load — ample time to shut down protected equipment if an outage occurs.



Ideally Suited For:

- Professional workstations.
- Small routers and bridges.
- Point-of-sale terminals.
- Other sensitive electronics.



	PSP350MT3-120U	PSP500MT3-120U
<b>Capacity (VA/W)</b>	350/210	500/300
<b>Net Weight, lb. (kg)</b>	6.4 (2.9)	8.8 (4.0)
<b>Dimensions - W x D x H, in. (mm)</b>	3.4 x 8.5 x 9.9 (87 x 215 x 251)	
<b>Input Voltage</b>	84-140VAC	
<b>Frequency</b>	50/60Hz ±5Hz	
<b>Output Voltage (Utility Power Normal)</b>	Typical 84-140VAC	
<b>Output Voltage (Battery Operation)</b>	120VAC ±5%	
<b>On-Battery Wave Form</b>	Stepped sinewave	
<b>Typical Recharge Time</b>	6-8 hours to 90%	
<b>Battery Run Time* - Full Load</b>	3-5 minutes	
<b>Battery Run Time* - Half Load</b>	10 minutes	
<b>Audible and Visual</b>	Audible alarm / LED	
<b>Backup Outlets</b>	NEMA 5-15R (3)	
<b>Surge Outlets</b>	NEMA 5-15R (1)	
<b>Operating Temperature, °F (°C)</b>	32 to 104 (0 to 40)	
<b>Agency**</b>		
<b>Safety</b>	UL 1778, c-UL Listed	
<b>EMC</b>	FCC Part 15 Class B IEC 61000-4-2 Electrostatic discharge IEC 61000-4-3 Radiated E-RFI fields IEC 61000-4-4 Fast E transients IEC 61000-4-5 Surges/Lightning IEC 61000-4-6 Conducted RFI ANSI C62.41 Category A Level 3 (surges)	
<b>Transportation</b>	ISTA Procedure 1A Certification	

